



Wymiary podstawy / FOOTPRINT

Oznaczenia / SIGNS :

Fh	Otwory mocujące FIXING HOLES	Ø18
G..	Uchwyty stóp antywibracyjnych VIBRATION DAMPER FOOT HOLDS	

Typ P.C. MODEL	Waga WEIGHT (kg)	Waga całkowita OPERATING WEIGHT (kg)	
50	587	590	
60	604	607	
70	614	617	
80	632	635	
90	643	646	
Dodatek Δ WEIGHT	Pompa obiegowa x1	16	18
Dodatek Δ WEIGHT	Pompy obiegowe x2	32	34

	G1 (kg)	G2 (kg)	G3 (kg)	G4 (kg)
50	159	164	155	112
60	164	169	160	115
70	166	171	162	117
80	171	176	167	121
90	174	179	170	123
50 1P	161	166	162	119
60 1P	166	171	167	122
70 1P	168	173	169	124
80 1P	173	178	174	128
90 1P	176	181	177	130
50 2P	167	172	170	127
60 2P	172	177	175	130
70 2P	174	179	177	132
80 2P	179	184	182	136
90 2P	182	187	185	138

Opis / Description :

Wymiary montażowe podstawy / MONTAGE DRAWING
ENERGYCAL AW PRO AT 50.2-90.2

VIESMANN



Skala-Scale
1/12,5

Data-Date
24\04\2014

- Wszelkie prawa zastrzeżone
- Reserved property, reproduction prohibited according to
existent laws. Copyright. MSQ-036R00