

## Moduły zewnętrzne

Vitocal 222-S	Typ	Przewód	Maks. długość przewo- du
Urządzenia 230 V	▪ AWBT-M	221.C04	3 x 2,5 mm <sup>2</sup>   29 m
	▪ AWBT-M-E	221.C06	3 x 2,5 mm <sup>2</sup>   29 m
	▪ AWBT-M-E-AC	221.C08	3 x 2,5 mm <sup>2</sup>   29 m
		221.C10	3 x 2,5 mm <sup>2</sup>   20 m
			<b>lub</b>
			3 x 4,0 mm <sup>2</sup>   32 m
	221.C13	3 x 2,5 mm <sup>2</sup>   20 m	
			<b>lub</b>
			3 x 4,0 mm <sup>2</sup>   32 m
	221.C16	3 x 2,5 mm <sup>2</sup>   20 m	
		<b>lub</b>	
		3 x 4,0 mm <sup>2</sup>   32 m	
Urządzenia 400 V	▪ AWBT	221.C10	5 x 2,5 mm <sup>2</sup>   30 m
	▪ AWBT-E	221.C13	5 x 2,5 mm <sup>2</sup>   30 m
	▪ AWBT-E-AC	221.C16	5 x 2,5 mm <sup>2</sup>   30 m